

BRAZED PLATE HEAT EXCHANGER | MODEL ABX400 | SUBMITTAL

File no: 113.60

Date: DECEMBER 21, 2020

Supersedes: 113.60

Date: MARCH 16, 2020

Job:		Representative:	Representative:			
		Order No:		Date:		
Engineer:		Submitted by:				
Contractor:		Approved by:				
QUANTITY	TAG NO.	MODEL NO.	COMMENTS			
-						

ABX - BRAZED PLATE HEAT EXCHANGERS

Armstrong's ABX brazed plate heat exchangers are designed to facilitate heat transfer between two media of different temperatures. ABX produces high heat transfer rates that allow for a compact, corrosion resistant and robust design.

DESCRIPTION

Number of plates (N):				
Design Pressure	435 psi (30 bar)			
Max Temperature	392°F/200°C			
Plate Material	316 ss			
Braze Material	Copper			
Connection Material	304 SS			

TYPICAL SPECIFICATION

Furnish and install on the plans and described herein, an Armstrong ABX400-_____ brazed plate heat exchanger. Each heat exchanger must be designed to have the capacity and pressure/temperature rating as detailed in the schedule. The heat exchanger must utilize 316L stainless steel plates and copper braze to separate the two fluids while transferring heat and preventing corrosion.

Each heat exchanger shall be Armstrong ABX400-_____ or approved equal.


CONNECTIONS

		Size - inch	Location	Rating	
-	Fluid 1 Inlet	3.00	A2	Grooved	
-	Fluid 1 Outlet	3.00	B1	Grooved	
-	Fluid 2 Inlet	3.00	A1	Grooved	
-	Fluid 2 Outlet	3.00	B2	Grooved	

2

DIMENSIONS

DIMENSIONS in inch (mm)			VOLUME	WEIGHT			
Α	В	С	D	Е	L	gals(ltrs)	lbs(kgs)
29.56	25.59	12.63	8.66			'	69.18 + (1.77 × N) lbs
(751)	(650)	(321)	(220)	(54)	(16 + 2.33N)	(N-1)*0.423 liters	31.38 + (0.805 × N) kgs



TORONTO

+1 416 755 2291

BUFFALO

+1 716 693 8813

BIRMINGHAM

+44 8444 145 145

MANCHESTER

+44 8444 145 145

BANGALORE

+91 80 4906 3555

SHANGHAI

+86 21 5237 0909

SÃO PAULO

+55 11 4785 1330

LYON

+33 4 26 83 78 74

DUBAI

+971 4 887 6775

MANNHEIM