

DESIGN ENVELOPE 6800 G | COMMERCIAL WATER BOOSTER | I240802 - I140802s | SUBMITTAL

File No: 106.00391EC
Date: APRIL 24, 2018
Supersedes: NEW
Date: NEW

Job: _____ Representative: _____
 _____ Order by: _____ Date: _____
 Engineer: _____ Submitted by: _____ Date: _____
 Contractor: _____ Approved by: _____ Date: _____

PUMP DESIGN DATA

No. of pumps: 2 Tag: _____ Series: 4700
 Total package capacity: _____ L/s (m³/h)
 Pump capacity: _____ L/s (m³/h)
 Head: _____ Bar (m) Liquid: _____
 Construction: Stainless steel 304

CONNECTION ORIENTATION

Suction Right* Left*
 Discharge Right* Left*

* When facing control panel

DRIVE DATA

Enclosure: IP66
 EMI/RFI control: Integrated filter designed to meet EN61800-3
 Harmonic suppression: Integrated DC link reactors
 Cooling: Fan-cooled through back channel
 Ambient temperature: -10°C to +45°C up to 1000 meters

OPTIONAL EQUIPMENT

Duty standby discharge transducer: Yes No
 BMS communication: BACnet MS/TP BACnet IP
 LonWorks
 Float switch: Yes No
 AV kit: No Potable water untied
 Potable water tied
 Overhead break tank: Yes No

SYSTEM CONSTRUCTION DATA

System description: Duplex
 Model: _____
 Header connections: Flanged
 Piping material: Stainless steel 304
 Valve type: Ball valve/butterfly valve and Check valve
 Setup: All duty Duty standby

MOTOR DESIGN DATA

kW: 5.5 RPM: 3600 Frame size: 90 Enclosure: TEFC
 Power supply: 400/3/50 V Efficiency: IE5


CONTROL PANEL SPECIFICATIONS

Enclosure rating: IP55
 HMI: Colour touch screen
 Low suction shutdown
 Main disconnect with interlock
 Fused motor protection
 Power on indication
 Motor run indication
 No-flow shutdown and automatic alternation
 Soft fill mode
 Pressure setback mode
 Field adjustable set points, alarms
 Flash memory storage
 Suction transducer included
 Modbus RTU serial communication


DESIGN ENVELOPE CAPABILITY DATA

| ENVELOPE CURVE NUMBER | PUMP | PRESSURE RATING in bar | MAX WORKING PRESSURE in bar | EACH MOTOR in kW | SUCTION E | DISCHARGE F | FLC in Amps | |
|----------------------------------|-----------------------------------|------------------------|-----------------------------|------------------|-----------|-------------|-------------|------|
| <input type="checkbox"/> I240802 | <input type="checkbox"/> I140802S | VMS-10:08 | PN16 | 12.94 | 5.5 | DN 50 | DN 50 | 11.6 |

I240802



I140802S



DIMENSION DATA

I240802 I140802S

| | |
|----------------|--------------|
| A: | 880 (34.65) |
| B: | 1560 (61.42) |
| C: | 899 (35.40) |
| D: | 500 (19.68) |
| G: | 145 (5.71) |
| H: | 348 (13.68) |
| J: | 386 (15.18) |
| K: | 733 (28.86) |
| L: | 898 (35.35) |
| M: | 820 (32.28) |
| N: | 427 (16.81) |
| P: | 413 (16.24) |
| R: | 450 (17.72) |
| T: | 130 (5.12) |
| WEIGHT: | 396.0 (873) |

Dimensions - mm (inches)

Weight - kg (lbs)

Note: Tolerances are 12 mm ($\pm 1/2"$) unless otherwise specified.

TORONTO
+1 416 755 2291

BUFFALO
+1 716 693 8813

BIRMINGHAM
+44 (0) 8444 145 145

MANCHESTER
+44 (0) 8444 145 145

BANGALORE
+91 (0) 80 4906 3555

SHANGHAI
+86 (0) 21 5237 0909

SÃO PAULO
+55 11 4781 5500

